



## DECLARATION OF PERFORMANCE

According Regulation CPR EU N°305/2011

No. 1022406801198

- Unique identification code of the product-type:  
**1022406801198 – Safety PLAST MINERAL EBP 4mm**
- Intended use/uses:  
**Bituminous Membrane for Waterproofing  
1m x 8m x 4mm membrane, with polyester carrier, APP modified bitumen. Mineral granules on top surface and plastic film finishing on lower surface. Torch on application. Application in multilayer systems as finishing layer.**
- Manufacturer:  
**TRP OOO TEGOLA ROOFING PRODUCTS  
142641, Moscow Oblast',  
Orekhovo Zuyevo Region, Davydovo, ul. Zavodskaya, corp.4  
Russian Federation**
- Authorised representative:  
**Not Applicable**
- System/s of AVCP:  
**System 2+**
- a) Harmonized standard:  
**EN 13707:2013**  
Notified Body/ies:  
**SGS, Notified Body N°1381, Certification N°1381-CPR-421**
- Declared Performances:

| Harmonized Technical Specification<br>EN 13707:2013  |  |             |           |                    |
|--|--|-------------|-----------|--------------------|
| Essential Characteristics                            | Unit   | Performance | Tolerance | Standard           |
| External Fire Resistance                             | -  | Broof (t1)  | -         | EN 13501-5         |
| Reaction to Fire                                     | -  | F           | -         | EN 13501-1         |
| Watertightness (Method A, 60kPa/24h)                 | -  | Pass        | -         | EN 1928            |
| Tensile Strength Length/Width                        | N/50mm   | 600/400     | +/-20%    | EN 12311-1         |
| Resistance to Static Loading                         | Kg   | >10         | MLV       | EN 12730           |
| Resistance to Impact                                 | mm   | >700        | MLV       | EN 12691           |
| Resistance to Tearing (Nail Method)                  | N  | >120        | MLV       | EN 12310-1         |
| Shear Resistance of Joints                           | N/50mm   | 500/300     | +/-20%    | EN 12317-1         |
| Durability: Flow Resistance at Elevated Temperatures | °C   | >110        | MLV       | EN 1296<br>EN 1110 |
| Durability: Artificial Aging Behavior                | -  | Pass        | -         | EN 1297            |
| Flexibility at Low Temperatures                      | °C   | <-10        | MLV       | EN 1109            |
| Dangerous Substances                                 | This product does not contain asbestos or tar. |             |           |                    |

- Appropriate Technical Documentation and/or Specific Technical Documentation:  
**Not Applicable**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Eng. Filippo Derighet  
Quality Engineer



Davydovo, 22/02/2016  
Rev. 02, 18/10/2018